

Power Supply DALI Downlight

BL TCI Power supply CC 220-240VAC 10-49VDC 350mA IP20 DALI

Article no.: 729026



BILTON LEDON
BETTER LIGHT

Oops – erwischt!

Hier folgt bald das gewünschte Bild.

TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 10-49VDC. Output current 350mA. DALI control signal. Protection class IP20. Protection class II. Dimensions LxWxH = 108x52x22mm



MECHANICAL DATA

Power Supply DALI Downlight

Width [mm]
Length [mm]

52
108



BETTER LIGHT

Height [mm] 22
Power supply CC 220-240VAC 10-49VDC 350mA IP20 DALI

Control signal DALI
Article no. 729026

DALI

Degree of protection (IP)

IP20

Core cross section

0,5 - 1,5

ELECTRICAL DATA

Protection class

III

Voltage type

AC

Control signal

DALI

Input voltage range

220 - 240

Output power range

12,5

Frequency supply voltage (range)

50 - 60

Output current range

72

Dimming DALI

yes

CONNECTION

Core cross section

0,5 - 1,5

TEMPERATURE TECHNICAL DATA

Lifespan at 20 °C

50000

PACKAGING INFORMATION

State of origin

IT

Net weight [g]

106

Gross weight [g]

106

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at