

# Power Supply switchable Downlight

BL TCI Power supply CC 220-240VAC 15-50VDC 350mA IP20 1-10V PUSH

Article no.: 729022



**BILTON LEDON**  
BETTER LIGHT

Oops – erwischt!

**Hier folgt bald das gewünschte Bild.**

---

TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 15-50VDC. Output current 350mA. Control signal 1-10V or switch-dimming. Protection class IP20. Protection class II. Dimensions LxWxH = 108x52x22mm



MECHANICAL DATA

# Power Supply switchable Downlight

Width  
Length

52  
108



BETTER LIGHT

Height  
Control signal  
Article no. 729022

22

Analog 1 - 10 V

Degree of protection (IP)

IP20

Core cross section

0,5 - 1,5

## ELECTRICAL DATA

Protection class

III

Voltage type

AC

Control signal

Analog 1 - 10 V

Input voltage range

220 - 240

Output power range

12,5

Frequency supply voltage (range)

50 - 60

Output current range

72

Dimming 1-10 V

yes

Dimming Touch and Dim

yes

## CONNECTION

Core cross section

0,5 - 1,5

## TEMPERATURE TECHNICAL DATA

Lifespan at 20 °C

50000

## PACKAGING INFORMATION

State of origin

IT

Net weight [g]

108

Gross weight [g]

108

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: [www.better-light.at](http://www.better-light.at)

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: [www.better-light.at](http://www.better-light.at)