

Power Supply switchable Downlight

BL TRI Power supply CC 220-240VAC 25-50VDC 700mA IP20 on/off

Article no.: 729042



TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 25-50VDC. Output current 700mA. Protection class IP20. Protection class II. Dimensions LxWxH = 157x43x30mm



Power Supply switchable Downlight

BL TRI Power supply CC 220-240VAC 25-50VDC 700mA IP20 on/off

Article no.: 729042



MECHANICAL DATA

Width	43
Length	157
Height	30
Control signal	ohne
Degree of protection (IP)	IP20
Core cross section	0,5 - 1,5

ELECTRICAL DATA

Protection class	III
Voltage type	DC
Control signal	ohne
Input voltage range	220 - 240
Output power range	18,5
Frequency supply voltage (range)	50 - 60
Output current range	102

CONNECTION

Core cross section	0,5 - 1,5
--------------------	-----------

TEMPERATURE TECHNICAL DATA

Lifespan at 20 °C	50000
-------------------	-------

PACKAGING INFORMATION

State of origin	RS
Net weight [g]	105
Gross weight [g]	105
Net width [mm]	43
Net height [mm]	30
Net length [mm]	157

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at