

Power Supply switchable Downlight

BL TRI Power supply unit CC 220-240VAC 25-43VDC 350mA IP20 on/off

Article no.: 729027



TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 25-43VDC. Output current 350mA. Protection class IP20. Protection class II. Dimensions LxWxH = 100x43x22.5mm



Power Supply switchable Downlight

BL TRI Power supply unit CC 220-240VAC 25-43VDC 350mA IP20 on/off

Article no.: 729027



MECHANICAL DATA

Width	43
Length	100
Height	22.5
Control signal	ohne
Degree of protection (IP)	IP20
Core cross section	0,5 - 1,5

ELECTRICAL DATA

Protection class	III
Voltage type	AC
Lamp voltage	230
Control signal	ohne
Input voltage range	220 - 240
Output power range	12,5
Frequency supply voltage (range)	50 - 60

LIGHT TECHNICAL DATA

Colour temperature	-
--------------------	---

CONNECTION

Core cross section	0,5 - 1,5
--------------------	-----------

PACKAGING INFORMATION

State of origin	CN
Net weight [g]	58
Gross weight [g]	58

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at