Power Supply switchable Downlight

BL TRI Power supply unit CC 220-240VAC 25-43VDC 350mA IP20 on/off
Article no.: 729027

BETTER LIGHT

BILTON LEDON
BETTER LIGHT

Oops – erwischt!

Hier folgt bald das gewünschte Bild.

TENDER TEXT

Constant current power supply unit. Input voltage 220-240VAC. Output voltage 25-43VDC. Output current 350mA. Protection class IP20. Protection class II. Dimensions LxWxH = 100x43x22.5mm



PACKAGING INFORMATION

State of origin	CN
Net weight [g]	58
Gross weight [g]	58

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.