

Panel Pure

LED DRIVER 220-240V CC 1000mA 9-42VDC DALI

Article no.: 719239



DALI / Switch

Control signal

IP20

Degree of protection (IP)

II

Protection class

1000

Output current range

TENDER TEXT

incl. connection cable for Panel Gen5 Pure



MECHANICAL DATA

Housing	Kunststoffgehäuse
Width	44
Length	137.5
Height	23
Model	dynamisch
Control signal	DALI / Switch
With overheating protection	nein
Suitable for outdoor use	nein
Degree of protection (IP)	IP20
Core cross section	0,5 - 1,5

ELECTRICAL DATA

Protection class	II
Control signal	DALI / Switch
With overheating protection	nein
Input voltage range	198 - 264
Output voltage range	9 - 42
Output current range	1000
Overload protection	yes
Standby power consumption (solstandby)	0.45
Suitable for constant current	yes
Suitable for constant voltage	nein
Suitable for DC-voltage (primary side)	yes
Dimming DALI	yes

CONNECTION

Core cross section	0,5 - 1,5
--------------------	-----------

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	- 20 ... + 90
Ambient temperature during operating	- 20 ... + 45

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	85044083
Net width [mm]	44
Net height [mm]	23
Net length [mm]	137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. We do not accept any liability for errors or omissions. Please make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

Panel Pure

LED DRIVER 220-240V AC 1000mA 9-42VDC DALI
Article no.: 719239

