

Downlight Pure

LED DRIVER 220-240V CC 350mA 27-45VDC ON/OFF

Article no.: 729178




TENDER TEXT

incl. connection cable for FDL180



MECHANICAL DATA

Housing	Kunststoffgehäuse	Downlight Pure	
Width	44		
Length	137.5	LED DRIVER 220-240V CC 350mA 27-45VDC ON/OFF	BETTER LIGHT
Height	23		
Article no.:	729178		
Model	Static		
Control signal	ohne		
With overheating protection	nein		
Suitable for outdoor use	nein		
Degree of protection (IP)	IP20		
Core cross section	0,5 - 1,5		

ELECTRICAL DATA

Protection class	II
Control signal	ohne
With overheating protection	nein
Input voltage range	198 - 264
Output voltage range	27 - 45
Output current range	350
Overload protection	yes
Standby power consumption (solstandby)	0.5
Suitable for constant current	yes
Suitable for constant voltage	nein
Suitable for DC-voltage (primary side)	yes
No dim function	yes

CONNECTION

Core cross section	0,5 - 1,5
--------------------	-----------

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	- 40 ... + 85
Ambient temperature during operating	- 20 ... + 45

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	85044083
Net width [mm]	44
Net height [mm]	23
Net length [mm]	137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at