

Downlight Office

LED DRIVER 220-240V CC 450mA 27-45VDC ON/OFF Office DL

Article no.: 729159



TENDER TEXT

incl. connection cable for Office DL



MECHANICAL DATA

Housing	Kunststoffgehäuse
Width	44
Length	137.5
Height	23
Model	Static
Control signal	ohne
With overheating protection	nein
Suitable for outdoor use	nein
Degree of protection (IP)	IP20
Core cross section	0,5 - 1,5

ELECTRICAL DATA

Protection class	II
Control signal	ohne
With overheating protection	nein
Input voltage range	198 - 264
Output voltage range	27 - 45
Output current range	450
Overload protection	yes
Standby power consumption (solstandby)	0.5
Suitable for constant current	yes
Suitable for constant voltage	nein
Suitable for DC-voltage (primary side)	yes
No dim function	yes

CONNECTION

Core cross section	0,5 - 1,5
--------------------	-----------

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature	- 40 ... + 85
Ambient temperature during operating	- 20 ... + 45

PACKAGING INFORMATION

State of origin	CN
Customs tariff number	85044083
Net width [mm]	44
Net height [mm]	23
Net length [mm]	137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

Downlight Office

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out in the best of our knowledge. We do not accept any liability for errors and omissions. Customers are advised to always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at

LED DRIVER 220-240V CC 450mA 27-45VDC ON/OFF Office DL

Article no.: 729159

