

Downlight Protected

LED DRIVER 220-240V CC 450mA 27-45VDC ON/OFF Protected DL

Article no.: 729165



ohne

Control signal

IP20

Degree of protection (IP)

450

Output current range

TENDER TEXT

for DL Protected 145mm BILTON LEDON Technology Downlight Protected Article 729165 The power supply can be used for a output voltage range of 27-45 . Constant current 450 . The supply voltage of the power supply is 198 - 264 and has a IP20 protection type and protection class II . Control signal ohne . Dimensions (L x W x H): 137.5 x 44 x 23



Downlight Protected

LED DRIVER 220-240V CC 450mA 27-45VDC ON/OFF Protected DL

Article no.: 729165



PACKAGING INFORMATION

State of origin	CN
Customs tariff number	85044083
Net width [mm]	44
Net height [mm]	23
Net length [mm]	137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at