Downlight Protected

LED DRIVER 220-240V CC 450mA 9-45VDC DALI Protected DL
Article no.: 729163



DALI / Switch	IP20	450	Yes
Control signal	Degree of protection (IP)	Output current range	Dimming DALI

TENDER TEXT

for DL Protected 145mm BILTON LEDON Technology Downlight Protected Article 729163 The power supply can be used for a output voltage range of 9-45 . Constant current 450 . The supply voltage of the power supply is 198 - 264 and has a IP20 protection type and protection class II . Control signal DALI/Switch . Dimensions (L x W x H): 137.5 x 44 x 23

PACKAGING INFORMATION

Downlight Protected

LED DRIVER 220-240V CC 450mA 9-45VDC DALI Protected DL

Article no.: 729163

State of origin	CN
Customs tariff number	85044083
Net width [mm]	44
Net height [mm]	23
Net length [mm]	137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at