

Power Supply switchable Downlight

LED DRIVER 220-240V CC 700mA 27-45VDC ON/OFF X

Article no.: 729158



TENDER TEXT

incl. connection cable for FDL240



MECHANICAL DATA

Power Supply switchable Downlight

Housing
Width

Kunststoffgehäuse
44



BETTER LIGHT

LED DRIVER 220-240V CC 700mA 27-45VDC ON/OFF X

Article no.: 729158

23

Model

Static

Control signal

ohne

With overheating protection

nein

Suitable for outdoor use

nein

Degree of protection (IP)

IP20

Core cross section

0,5 - 1,5

ELECTRICAL DATA

Protection class

II

Control signal

ohne

With overheating protection

nein

Input voltage range

198 - 264

Output voltage range

27 - 45

Output current range

700

Overload protection

yes

Standby power consumption (solstandby)

0.5

Suitable for constant current

yes

Suitable for constant voltage

nein

Suitable for DC-voltage (primary side)

yes

No dim function

yes

CONNECTION

Core cross section

0,5 - 1,5

TEMPERATURE TECHNICAL DATA

Ambient/storage temperature

- 40 ... + 85

Ambient temperature during operating

- 20 ... + 45

PACKAGING INFORMATION

State of origin

CN

Customs tariff number

85044083

Net width [mm]

44

Net height [mm]

23

Net length [mm]

137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at