Downlight Pure

LED DRIVER 220-240V CC 700mA 27-45VDC ON/OFF

Article no.: 729174

BETTER LIGHT



ohne

Control signal

IP20

Degree of protection (IP)

700

Output current range

TENDER TEXT

incl. connection cable for FDL240 BILTON LEDON Technology Downlight Pure Article 729174 The power supply can be used for a output voltage range of 27-45 . Constant current 700 . The supply voltage of the power supply is 198 - 264 and has a IP20 protection type and protection class II . Control signal ohne . Dimensions (L x W x H): 137.5 x 44 x 23

IP20 RoHS COMPLIANT 2002/95/EC CE

PACKAGING INFORMATION

© BILTON LEDON Technology | www.better-light.at
Gewerbepark Harham 2, 5760 Saalfelden | Austria | Phone: +43 6582 71164 | Mail: office@bltechnology.at
Version: 20261119 | Errors and printing errors are reserved.

Downlight Pure

LED DRIVER 220-240V CC 700mA 27-45VDC ON/OFF

Article no.: 729174

State of origin	CN
Customs tariff number	85044083
Net width [mm]	44
Net height [mm]	23
Net length [mm]	137.5

SAFETY INFORMATION: Read the safety and installation instructions carefully and completely before commissioning. The operating instructions can be found at: www.better-light.at

DISCLAIMER OF WARRANTY: The technical information corresponds to the status at the time of printing and have been worked out to the best of our knowledge. However, errors and printing errors are reserved. Make sure that you always use the latest version of the data sheets. The latest data sheet can be found at: www.better-light.at